

PRODUCT NAME	CTXF-C			CTXF20C5V1B			CTXF25C5V1B			CTXF35C5V1B		
Power input	Cooling		Nom.	kW	0.017	0.019	0.032					
	Heating		Nom.	kW	0.02	0.02	0.032					
Casing	Colour				White	White	White					
Dimensions	Unit	Height	mm	286	286	286						
		Width	mm	770	770	770						
		Depth	mm	225	225	225						
	Packed unit	Height	mm	305	305	305						
		Width	mm	830	830	830						
Depth		mm	360	360	360							
Weight	Unit			kg	8.5	8	9					
	Packed unit			kg	11	10	11					
Packing	Weight			kg	2	2	2					
Heat exchanger	Length			mm	610	610	610					
	Rows		Quantity		2	2	2					
	Fin pitch			mm	1.4	1.4	1.4					
	Stages		Quantity		18	18	18					
	Tube type				ø5 Hi-XB	ø5 Hi-XB	ø5 Hi-XB					
	Fin		Type		ML fin (Multi louver)	ML fin (Multi louver)	ML fin (Multi louver)					
Heat exchanger 2	Length			mm			600					
	Rows		Quantity				1					
	Fin pitch			mm			1.4					
	Stages		Quantity				4					
Fan	Type				Cross flow fan	Cross flow fan	Cross flow fan					
	Quantity				1	1	1					
Air flow rate	Cooling	High	m³/min	9.8	10.1	11.5						
		High	cfm	346	357	406						
	Medium	m³/min	8	8	8							
		Medium	cfm	279	222	293						
	Low	m³/min	5.9	6.1	6.3							
		Low	cfm	208	215	226						
	Silent operation	m³/min	4.4	4.4	4.5							
		Silent operation	cfm	155	155	159						
	Heating	High	m³/min	10.3	10.3	11.5						
		High	cfm	364	364	406						
		Medium	m³/min	8.4	8.6	9						
		Medium	cfm	297	304	318						
		Low	m³/min	6.5	6.7	7						
		Low	cfm	230	237	247						
Silent operation		m³/min	5.3	5.3	5.3							
Silent operation		cfm	187	187	187							
Fan motor	Model				MM6K11S20VA	MM6K11S20VA	MM6K11S20VA					
	Speed				5 + silent, + auto	5 + silent, + auto	5 + silent, + auto					
	Cooling	High	rpm	1000	1020	1140						
		Medium	rpm	830	850	870						
		Low	rpm	660	680	700						
		Silent operation	rpm	530	530	540						
	Heating	High	rpm	1040	1040	1140						
		Medium	rpm	880	890	930						
		Low	rpm	710	730	760						
		Silent operation	rpm	610	610	610						
	Output		Rated	W	22	22	22					
	Sound power level	Cooling			dB(A)	55	55	58				
		Heating			dB(A)	55	55	58				
	Sound pressure level	Cooling	High	dB(A)	39	40	43					
Medium			dB(A)	33	33	34						
Low			dB(A)	25	26	27						
Silent operation			dB(A)	20	20	20						
Heating		High	dB(A)	39	40	40						
		Medium	dB(A)	34	34	35						
		Low	dB(A)	28	28	29						
		Silent operation	dB(A)	21	21	21						
IP class				IP-X0	IP-X0	IP-X0						
Piping connections	Liquid	OD	mm	6.35	6.35	6.35						
	Gas	OD	mm	9.5	9.5	9.5						
	Drain			18	18	18						
	Heat insulation				Both liquid and gas pipes	Both liquid and gas pipes	Both liquid and gas pipes					
Air filter	Type			Removable / washable	Removable / washable	Removable / washable						
Air direction control				Right, Left, Horizontal, Downward	Right, Left, Horizontal, Downward	Right, Left, Horizontal, Downward						
Temperature control				Microcomputer control	Microcomputer control	Microcomputer control						
Control systems	Infrared remote control				ARC470A1	ARC470A1	ARC470A1					
	Wired remote control				BRC073A1	BRC073A1	BRC073A1					
Standard Accessories	Installation manual				1	1	1					
	AAA dry-cell batteries				2	2	2					
	Operation manual				1	1	1					
	Batteries				1	1	1					
	Indoor unit fixing screws				2	2	2					
	Infrared remote control				1	1	1					
	Mounting plate				1	1	1					
	Remote control holder				1	1	1					
	Power supply	Phase				1~	1~	1~				
		Power supply--Frequency	Frequency			50	50	50				
Power supply--Voltage		Voltage			220-440	220-440	220-440					