

FTXTA-CW + RXTA-C



Indoor unit		FTXTA		30CW	
Dimensions	Unit	HeightxWidthxDPTH		mm	
				295 x798 x189	
Weight	Unit			kg	
				12	
Air filter	Type			Removable / washable	
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/High	m ³ /min	4.9 / 6.0 / 9.0 / 13.1
		Heating	Silent operation / Low / Medium / High	m ³ /min	5.0 / 5.8 / 8.2 / 12.3
Sound power level	Cooling			dBA	
	Heating			dBA	
				60.0	
Sound pressure level	Cooling	Silent operation/Low/High		dBA	
	Heating	Silent operation/Low/High		dBA	
				20.0 / 25.0 / 43.0	
				19.0 / 24.0 / 41.0	
Control systems	Infrared remote control				ARC466A84
	Wired remote control				BRC073A4


Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m | See separate drawing for electrical data

Outdoor unit		RXTA		30C	
Dimensions	Unit	HeightxWidthxDPTH		mm	
				605 x930 x376	
Weight	Unit			kg	
				42	
Sound power level	Cooling			dBA	
	Heating			dBA	
				60	
Sound pressure level	Cooling	Nom.		dBA	
	Heating	Nom.		dBA	
				48.0	
				49.0	
Operation range	Cooling	Ambient	Min.-Max.	°CDB	
	Heating	Ambient	Min.-Max.	°CWB	
				-10 ~-46	
				-31 ~-18	
Refrigerant	Type			R-32	
	GWP			675.0	
	Charge			kg/TCO ₂ Eq	
				0.97 / 0.66	
Piping connections	Liquid	OD		mm	
	Gas	OD		mm	
	Piping length	OU - IU	Max.	m	
	Additional refrigerant charge			kg/m	
	Level difference IU - OU	Max.		m	
				6.35	
				9.50	
				20	
				0.02 (for piping length exceeding 10m)	
				15.0	
Power supply	Phase/Frequency/Voltage				Hz/V
					1~/50 /220-240
Current - 50Hz	Maximum fuse amps (MFA)				A
					16

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

Efficiency data		FTXTA + RXTA		30CW + 30C	
Cooling capacity	Min./Nom./Max.	kW		1.2 / 3.0 / 4.6	
Heating capacity	Min./Nom./Max.	kW		0.8 / 3.2 / 7.10	
Power input	Cooling	Nom.		kW	
	Heating	Nom.		kW	
				0.62	
				0.64	
Space cooling	Energy efficiency class				A+++
	Capacity	Pdesign		kW	
	SEER				
	Annual energy consumption			kWh/a	
				3.00	
				8.75	
				120	
Space heating (Average climate)	Energy efficiency class				A+++
	Capacity	Pdesign		kW	
	SCOP/A				
	Annual energy consumption			kWh/a	
				3.00	
				5.17	
				812	
Space heating (Cold climate)	Energy efficiency class				A+
	Capacity	Pdesignh		kW	
	Annual energy consumption			kWh/a	
	SCOP/C				
				4.38	
				2,248	
				4.09	
Nominal efficiency	EER			4.89	
	COP			5.01	
	Annual energy consumption			kWh	
	Energy labeling Directive	Cooling/Heating			
				310	
				A/A	
Current - 50Hz	Maximum fuse amps (MFA)				A
					16

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



ECPN23-062

08/2023



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: www.eurovent-certification.com

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

