

2 Specifications

2 - 1 Specifications

Technical specifications				EPVX10S18A4V + EPSK06AV3	EPVX10S23A4V + EPSK06AV3	EPVX10S18A4V + EPSK08AV3	EPVX10S23A4V + EPSK08AV3	EPVX10S18A4V + EPSK10AV3	EPVX10S23A4V + EPSK10AV3			
Space heating 	Cold climate water outlet 35°C	D Condition (12°CDB/ B/11°CWB)	PERd	%	308.4		314.2		319.3			
			Tol (tem- perature operating limit)	COPd		2.18		5.1				
			Pdh	kW	4.2		87					
		PERd	%	87.1				87				
		TOL	°C			-22						
		WTOL	°C			35						
		G Condition (-15°CDB/-)	COPd		2.87		2.75		2.65			
			Pdh	kW	5.1		6		6.9			
			PERd	%	114.8		110.1		105.8			
	Tbiv (bivalent tempera- ture)	COPd		2.87		2.75		2.65				
		Pdh	kW	5.1		6		6.9				
		PERd	%	114.8		110.1		105.8				
	Rated heat output sup- plementary capacity	Psup (at Tdesign -22°C)	Tbiv	°C			-15					
				kW	2.2		2.4		3.4			
	Warm climate water outlet 35°C	General	Annual energy consumption		kWh	1,364		1,561		1,755		
				ηs (Seasonal space heating efficiency)		%	252		254		256	
					Prated at 2°C	kW	6.5		7.5		8.5	
B Condition (2°CDB/ B/1°CWB)		Cdh (Degradation heating)	COPd				4.39					
			Pdh	kW			5.2					
			PERd	%			175.4					
C Condition (7°CDB/ B/6°CWB)		Cdh (Degradation heating)	COPd		5.88		5.86		5.84			
			Pdh	kW	4.1		5		5.9			
			PERd	%	235.4		234.6		233.7			
Tbiv (bivalent tempera- ture)		COPd			4.85		4.79		4.72			
			Pdh	kW	5.5		6.3		7.1			
			PERd	%	194.2		191.4		188.7			
D Condition (12°CDB/ B/11°CWB)		Cdh (Degradation heating)	Tbiv	°C			4					
					7.81		8		8.18			
			Pdh	kW	2.9		319.8		327.2			
PERd		%	312.4									

(1)Condition: Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) |
 (2)Cooling: EW 12°C; LW 7°C; ambient conditions: 35°CDB |
 (3)Cooling: EW 23°C; LW 18°C; ambient conditions: 35°CDB

Technical specifications				EPVX10S18A9W + EPSK06AV3	EPVX10S23A9W + EPSK06AV3	EPVX10S18A9W + EPSK08AV3	EPVX10S23A9W + EPSK08AV3	EPVX10S18A9W + EPSK10AV3	EPVX10S23A9W + EPSK10AV3
Indoor unit				EPVX10S18AJ9W	EPVX10S23AJ9W	EPVX10S18AJ9W	EPVX10S23AJ9W	EPVX10S18AJ9W	EPVX10S23AJ9W
Outdoor unit				EPSK06ARV3		EPSK08ARV3		EPSK10ARV3	
Heating capacity	Nom.		kW	5.81 (1)		7.62 (1)		8.11 (1)	
Cooling capacity	Nom.		kW	6.00 (2) / 6.37 (3)		6.89 (2) / 6.37 (3)		7.84 (2) / 6.37 (3)	
Power input	Heating	Nom.	kW	1.12 (1)		1.52 (1)		1.64 (1)	
	Cooling	Nom.	kW	1.55 (2) / 1.13 (3)		1.85 (2) / 1.13 (3)		2.17 (2) / 1.13 (3)	
Domestic hot water from 10°C to 50°C	Nom.		kWh	2.35	2.89	2.35	2.89	2.35	2.89
				1h 27min		1h 58min		1h 27min	
Heat up time from 10°C to 50°C				1h 27min		1h 58min		1h 27min	
COP				5.19 (1)		5.01 (1)		4.94 (1)	
EER				3.87 (2) / 5.63 (3)		3.73 (2) / 5.63 (3)		3.62 (2) / 5.63 (3)	
Pump	Nominal ESP	Heating unit	kPa	60.6					

2 Specifications

2 - 1 Specifications

2

Technical specifications			EPVX10S18A9W + EPSK06AV3	EPVX10S23A9W + EPSK06AV3	EPVX10S18A9W + EPSK08AV3	EPVX10S23A9W + EPSK08AV3	EPVX10S18A9W + EPSK10AV3	EPVX10S23A9W + EPSK10AV3		
General	Supplier/Manufacturer details	Name and address	Daikin Europe N.V. - Zandvoordestraat 300, 8400 Oostende, Belgium							
		Name or trademark	Daikin Europe N.V.							
	Product description	Air-to-water heat pump		Yes						
		Brine-to-water heat pump		No						
		Heat pump combination heater		No						
		Low-temperature heat pump		No						
		Supplementary heater integrated		Yes						
		Water-to-water heat pump		No						
	LW(A) Sound power level (according to EN14825)	dB(A)	dB(A)	45						
	LW(A) Sound power level (according to EN14825)	dB(A)	dB(A)	45			47			
Sound condition Ecodesign and energy label			Sound power in heating mode, measured according to the EN12102 under conditions of the EN14825. Ecodesign sound level is not representing the maximum sound level of this product							
Space heating general	Other	Capacity control	Inverter							
		Pck (Crankcase heater mode)	kW	0						
		Poff (Off mode)	kW	0.021						
		Psb (Standby mode)	kW	0.021						
		Pto (Thermostat off)	kW	0.021						
Domestic hot water heating	General	Declared load profile	L							
Space heating general	Integrated supplementary heater	Psup	kW	9						
		Type of energy input		Electrical						
Domestic hot water heating	Average climate	AEC (Annual electricity consumption)	kWh	873						
		COPdhw		2.93						
		Heat up time		1h 13min	1h 39min	1h 13min	1h 39min	1h 13min	1h 39min	
		Mixed water at 40°C	l	203.6	253.3	203.6	253.3	203.6	253.3	
		η _{wh} (water heating efficiency)	%	117						
		Qelec (Daily electricity consumption)	kWh	3.975						
Domestic hot water heating	Average climate	Reference hot water temperature	°C	47	47.4	47	47.4	47	47.4	
		Stand-by power input	W	42.1						
		Water heating energy efficiency class		A+						
		Cold climate	AEC (Annual electricity consumption)	kWh	1,014					
			COPdhw		2.52					
			Heat up time		1h 13min	1h 39min	1h 13min	1h 39min	1h 13min	1h 39min
	Mixed water at 40°C		l	203.6	253.3	203.6	253.3	203.6	253.3	
	η _{wh} (water heating efficiency)		%	101						
	Qelec (Daily electricity consumption)		kWh	4.616						
	Warm climate	Reference hot water temperature	°C	47	47.4	47	47.4	47	47.4	
		Stand-by power input	W	45.9						
		AEC (Annual electricity consumption)	kWh	759						
COPdhw			3.37							
Heat up time			1h 13min	1h 36min	1h 13min	1h 36min	1h 13min	1h 36min		
Mixed water at 40°C		l	203.6	253.3	203.6	253.3	203.6	253.3		
	η _{wh} (water heating efficiency)	%	135							
	Qelec (Daily electricity consumption)	kWh	3.457							
	Reference hot water temperature	°C	47	47.4	47	47.4	47	47.4		
	Stand-by power input	W	38.1							

2 Specifications


2 - 1 Specifications

Technical specifications				EPVX10S18A9W + EPSK06AV3	EPVX10S23A9W + EPSK06AV3	EPVX10S18A9W + EPSK08AV3	EPVX10S23A9W + EPSK08AV3	EPVX10S18A9W + EPSK10AV3	EPVX10S23A9W + EPSK10AV3			
Space heating 	Average climate water outlet 55°C	General	Annual energy consumption	kWh	3,438		3,903		4,363			
			ηs (Seasonal space heating efficiency)	%	153		156		158			
			Prated at -10°C	kW	6.5		7.5		8.5			
			SCOP		3.91		3.97		4.02			
			Seasonal space heating eff. class				A+++					
			A Condition (-7°CDB/-8°CWB)	Cdh (Degradation heating)			1					
				COPd		2.65		2.64		2.62		
				Pdh	kW	5.7		6.6		7.4		
				PERd	%	106		105.5		104.9		
			B Condition (2°CDB/1°CWB)	Cdh (Degradation heating)			1					
				COPd		3.86		3.92		3.98		
				Pdh	kW	3.5		4.1		4.7		
				PERd	%	154.4		156.8		159.1		
			C Condition (7°CDB/6°CWB)	Cdh (Degradation heating)			1					
				COPd		4.68		4.8		4.93		
				Pdh	kW	2.3		2.6		2.9		
				PERd	%	187.2		192.1		197		
			D Condition (12°CDB/11°CWB)	Cdh (Degradation heating)			1					
			Space heating 	Average climate water outlet 55°C	D Condition (12°CDB/11°CWB)	COPd		6.38		6.45		6.52
						Pdh	kW			2.8		
PERd	%	255.1					258		260.8			
Tol (temperature operating limit)	COPd					2.38		2.33		2.28		
	Pdh	kW				6.2		7.4		8.4		
	PERd	%				95.1		93		91.1		
	TOL	°C						-10				
	WTOL	°C						55				
Rated heat output supplementary capacity	Psup (at Tdesign -10°C)	kW				0.3				0		
	Tbiv (bivalent temperature)	COPd					2.65		2.33		2.28	
		Pdh				kW	5.7		7.4		8.4	
		PERd				%	106		93		91.1	
		Tbiv				°C	-7			-10		
Cold climate water outlet 55°C	General	Annual energy consumption				kWh	4,952		5,360		5,968	
		ηs (Seasonal space heating efficiency)				%	126		135		137	
		Prated at -22°C				kW	6.5		7.5		8.5	
		A Condition (-7°CDB/-8°CWB)				Cdh (Degradation heating)			1			
						COPd		2.94		2.98		3.01
						Pdh	kW	3.7		4.5		5.2
						PERd	%	117.7		119.1		120.5
		B Condition (2°CDB/1°CWB)	Cdh (Degradation heating)			1						
			COPd		3.79		3.99		4.18			
			Pdh	kW	2.3		2.9		3.4			
			PERd	%	151.6		159.5		167.4			
		C Condition (7°CDB/6°CWB)	Cdh (Degradation heating)			1						
			COPd		5.06		5.09		5.11			
			Pdh	kW			2.4					
			PERd	%	202.5		203.4		204.2			
		D Condition (12°CDB/11°CWB)	COPd		6.72		6.55		6.38			
			Pdh	kW			2.9					
			PERd	%	268.9		262		255			
		Tol (temperature operating limit)	COPd				1.71					
			Pdh	kW	4.5			5.5				
PERd	%				68.5							
TOL	°C				-22							
WTOL	°C				55							
G Condition (-15°CDB/-)	COPd		2.3		2.24		2.19					

2 Specifications

2 - 1 Specifications

2

Technical specifications				EPVX10S18A9W + EPSK06AV3	EPVX10S23A9W + EPSK06AV3	EPVX10S18A9W + EPSK08AV3	EPVX10S23A9W + EPSK08AV3	EPVX10S18A9W + EPSK10AV3	EPVX10S23A9W + EPSK10AV3	
Space heating 	Cold climate water outlet	G Condition	Pdh	kW	5.4		6.1		6.8	
		(-15°CDB/-)	PERd	%	91.8		89.6		87.4	
	55°C	Tbiv (bivalent tempera- ture)	COPd		2.3		2.24		2.19	
			Pdh	kW	5.4		6.1		6.8	
		PERd	%	91.8		89.6		87.4		
		Tbiv	°C			-15				
		Rated heat output sup- plementary capacity	Psup (at Tdesign -22°C)	kW	2			3		
	Warm climate water outlet	55°C	General	Annual energy consumption	kWh	1,868		2,317		2,491
				ηs (Seasonal space heating efficiency)	%	183		186		179
				Prated at 2°C	kW	6.5		8.2		8.5
		B Condition (2°CDB- B/1°CWB)	Cdhd (Degradation heating)				1			
			COPd				3.04			
		C Condition (7°CDB- B/6°CWB)	Cdhd (Degradation heating)	COPd		4.07		4.08		
				Pdh	kW	4.3		5.2		
				PERd	%	162.8		163.3		
		D Condition (12°CDB- B/11°CWB)	Cdhd (Degradation heating)	COPd		5.81		5.99		
				Pdh	kW			2.8		
	PERd			%	232.4		239.4			
	Average climate water outlet	35°C	General	Annual energy consumption	kWh	2,624		3,009		3,408
				ηs (Seasonal space heating efficiency)	%	202		203		
Prated at -10°C				kW	6.5		7.5		8.5	
SCOP					5.12		5.15			
A Condition (-7°CDB- B/-8°CWB)	Seasonal space heating eff. class				A+++					
	COPd		3.49		3.4		3.31			
B Condition (2°CDB- B/1°CWB)	Cdhd (Degradation heating)	COPd		5.04		5.06		5.07		
		Pdh	kW	3.4		4		4.6		

2 Specifications

2 - 1 Specifications

Technical specifications				EPVX10S18A9W + EPSK06AV3	EPVX10S23A9W + EPSK06AV3	EPVX10S18A9W + EPSK08AV3	EPVX10S23A9W + EPSK08AV3	EPVX10S18A9W + EPSK10AV3	EPVX10S23A9W + EPSK10AV3	
Space heating Average climate water outlet 35°C	B Condition (2°CDB/1°CWB)	PERd	%	201.5		202.2		203		
	C Condition (7°CDB/6°CWB)	Cdh (Degradation heating)			0.9				1	
		COPd		6.37		6.43		6.48		
		Pdh	kW	2.5		2.7		2.9		
		PERd	%	254.9		257		259.2		
	D Condition (12°CDB/11°CWB)	Cdh (Degradation heating)			0.9					
		COPd		8.15		8.23		8.3		
		Pdh	kW			2.9				
		PERd	%	325.9		329		332.2		
	Tol (temperature operating limit)	COPd		3.11		2.97		2.84		
		Pdh	kW	5.8		7.4		8.3		
		PERd	%	124.2		118.6		113.4		
		TOL	°C			-10				
	G Condition (-15°CDB/-)	WTOL	°C			35				
		PERd	%			0				
		Tbiv (bivalent temperature)	COPd		3.49		2.97		2.84	
			Pdh	kW	5.8		7.4		8.3	
	Rated heat output supplementary capacity	PERd	%	139.7		118.6		113.4		
		Tbiv	°C	-7			-10			
		Psup (at Tdesign -10°C)	kW	0.7			0			
	Cold climate water outlet 35°C	General	Annual energy consumption	kWh	3,643		4,304		4,948	
			ηs (Seasonal space heating efficiency)	%	170		169		166	
			Prated at -22°C	kW	6.4		7.5		8.5	
		A Condition (-7°CDB/-8°CWB)	COPd		3.86		3.84		3.83	
			Pdh	kW	4.2		4.6		5	
			PERd	%	154.4		153.7		153.1	
		B Condition (2°CDB/1°CWB)	Cdh (Degradation heating)			1				
			COPd		5.04		4.94		4.84	
			Pdh	kW	2.5		2.9		3.2	
			PERd	%	201.4		197.4		193.8	
C Condition (7°CDB/6°CWB)		Cdh (Degradation heating)			0.9					
		COPd		6.34		6.43		6.47		
		Pdh	kW			2.5				
D Condition (12°CDB/11°CWB)		PERd	%	253.6		257.3		258.8		
		Cdh (Degradation heating)			0.9					
		COPd		7.71		7.85		7.98		
		Pdh	kW			2.9				

2 Specifications

2 - 1 Specifications

2

Technical specifications				EPVX10S18A9W + EPSK06AV3	EPVX10S23A9W + EPSK06AV3	EPVX10S18A9W + EPSK08AV3	EPVX10S23A9W + EPSK08AV3	EPVX10S18A9W + EPSK10AV3	EPVX10S23A9W + EPSK10AV3
Space heating Cold climate water outlet 35°C	D Condition (12°CDB/ B/11°CWB)	PERd	%	308.4		314.2		319.3	
		Tol (tem- perature operating limit)	COPd			2.18		5.1	
		Pdh	kW	4.2			87		
		PERd	%	87.1					
		TOL	°C			-22			
		WTOL	°C			35			
	G Condition (-15°CDB/-)	COPd		2.87		2.75		2.65	
		Pdh	kW	5.1		6		6.9	
		PERd	%	114.8		110.1		105.8	
	Tbiv (bivalent tempera- ture)	COPd		2.87		2.75		2.65	
		Pdh	kW	5.1		6		6.9	
		PERd	%	114.8		110.1		105.8	
		Tbiv	°C			-15			
	Rated heat output sup- plementary capacity	Psup (at Tdesign -22°C)	kW	2.2		2.4		3.4	
	Warm climate water outlet 35°C	General	Annual energy consumption	kWh	1,364		1,561		1,755
			ηs (Seasonal space heating efficiency)	%	252		254		256
			Prated at 2°C	kW	6.5		7.5		8.5
		B Condition (2°CDB/ B/1°CWB)	Cdh (Degradation heating)				1		
			COPd				4.39		
			Pdh	kW			5.2		
		PERd	%			175.4			
C Condition (7°CDB/ B/6°CWB)		Cdh (Degradation heating)				1			
		COPd		5.88		5.86		5.84	
		Pdh	kW	4.1		5		5.9	
		PERd	%	235.4		234.6		233.7	
Tbiv (bivalent tempera- ture)		COPd		4.85		4.79		4.72	
		Pdh	kW	5.5		6.3		7.1	
		PERd	%	194.2		191.4		188.7	
		Tbiv	°C			4			
D Condition (12°CDB/ B/11°CWB)		Cdh (Degradation heating)				0.9			
		COPd		7.81		8		8.18	
		Pdh	kW			2.9			
		PERd	%	312.4		319.8		327.2	

(1)Condition: Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) |

(2)Cooling: EW 12°C; LW 7°C; ambient conditions: 35°CDB |

(3)Cooling: EW 23°C; LW 18°C; ambient conditions: 35°CDB

Technical Specifications				EPSK06AV3	EPSK08AV3	EPSK10AV3
Casing	Colour	Silver / Black				
	Material	Polyester painted galvanised steel plate				
Dimensions	Unit	Height	mm	1,123		
		Width	mm	1,330		
		Depth	mm	604		
	Packed unit	Height	mm	1,320		
		Width	mm	1,445		
		Depth	mm	775		
Weight	Unit	kg	174			
	Packed unit	kg	205			
Packing	Material	Carton / Wood (pallet) / PE (Straps)				
	Weight	kg	31.5			
Heat exchanger	Length	mm	1,210			
	Rows	Quantity	1			
		Fin pitch	mm	2.6		
	Passes	Quantity	6			
		Face area	m ²	1.29		
	Stages	Quantity	88			
	Tube type	Microchannel ..				
	Fin	Type	WF & Slit fin ..			
		Treatment	High Corrosion Resistant			
	Fan	Type	Propeller fan			
Quantity		1				
Air flow rate		Heating	High	m ³ /min	75.7	
		Cooling	High	m ³ /min	75.7	
Discharge direction	Horizontal					

2 Specifications

2 - 1 Specifications

Technical Specifications				EPSK06AV3	EPSK08AV3	EPSK10AV3	
Fan motor	Quantity			1			
	Model			Brushless DC motor			
	Output		W	68			
	Drive			Direct drive			
	Speed	Steps			12		
Heating		Nom.	rpm	415			
Cooling		Nom.	rpm	415			
Compressor	Quantity			1			
	Type			Hermetically sealed scroll compressor			
	Starting method			Inverter driven			
PED	Category			Category II			
Operation range	Heating	Min.	°CDB	-28			
		Max.	°CDB	25			
	Cooling	Min.	°CDB	10			
		Max.	°CDB	43			
	Domestic hot water	Max.	°CDB	40			
Min.		°CDB	-28				
PED	Most critical part	Name	Ps*V	Bar*l	Compressor 133		
Piping connections	inch		in		G 1 1/4" (male) ..		
	inch		in		G 1 1/4" (male) ..		
Sound power level	Heating	Nom.	dBA	45 (1)		47 (1)	
	Cooling	Nom.	dBA	52.2 (2)	53 (2)	53.2 (2)	
Sound pressure level	Heating	Nom.	dBA	32.6 (1)	32.4 (1)	32.8 (1)	
	Cooling	Nom.	dBA	36.9 (2)	37.2 (2)	37.3 (2)	
	Night quiet mode	Heating		dBA	29.5 (1)	30 (1)	33 (1)
		Cooling		dBA	30.8 (2)		
Refrigerant	Type		R-290				
	GWP		3				
	Charge		kg	1			
	Control		Expansion valve				
	Circuits	Quantity		1			
Refrigerant oil	Type		Refer to the name plate of the compressor				
	Charged volume		l	1.1			
Piping connections	Piping length	OU - IU	Max.	m	20 (3) / 30 (4)		
		High pressure side	Design pressure		bar		
	Level difference	IU - OU	Max.	m	10		
		Water circuit		Filter ball valve			
Defrost method						Reversed cycle	
Defrost control						Sensor for outdoor heat exchanger temperature	
Capacity control	Method		Inverter controlled				
Safety devices	Item	01	High pressure switch				
		02	Fuse				

Electrical Specifications				EPSK06AV3	EPSK08AV3	EPSK10AV3	
Power supply	Name		V3				
	Phase		1~				
	Frequency		Hz	50			
	Voltage		V	230			
	Voltage range	Min. cos phi	Nom.	-10		-	
			Max.	0.9		-	
		Max.	%	10	0.99		-
Current	kVa		kVA	Equipment complying with EN / IEC 61000-3-12			
	Recommended fuses		A	25			
	Inverter modulation	Min.	%	40	35	30	
Wiring connections	For power supply	Remark	See installation manual outdoor unit				
	For connection with indoor	Remark	See installation manual indoor unit				

(1) Measured at LWC 47-55°C ; Ta DB/WB 7°C/6°C. |

(2) Measured at LWC 12-7°C ; Ta 35°C. |

(3) 1/4" field piping |

(4) 1/2" field piping